

# Corncob Paddle LED



**Aamsco offers a simple alternative to conventional street and security lighting.**

## **Main Features:**

- Position oriented base
- No ballast necessary. Fast turn on; no warm-up or cold start problems
- Estimated life hours: >50,000
- Sturdy PCB housing with internal cooling fan
- 80% more energy saving compared with conventional HID, CFL, and incandescent lamps
- >85 CRI with great directionality
- 80 lumens per watt
- Universal burning positions

## **Specifications:**

- Operating voltage: 100-280V
- Frequency range: 50-60hz
- Color Temperatures: WW3000-3500K, CW4000-4500K, D6000-6500K
- Integrated Heat-Sink Design
- 3 year warranty
- ETL, CE & ROHS Certified
- Not for use on a dimmer or remote controls
- For use in open or enclosed fixtures\*\*\*

*\*\*\*In enclosed fixtures, ensure the lamp has enough space for heat dissipation. This will ensure lumen maintenance and extend its working life. When products are used in outdoor fixtures, ensure the space is waterproof and well ventilated. If there is a ballast in the existing fixture, simply disconnect or bypass when installing Corncob LED retrofit lamps.*

**Commercial – Hospitality – Retail – Residential – Custom**

**AAMSCO LIGHTING, INC.**

100 Lamp Light Circle | Summerville, SC 29483

Phone 843-278-0000 | Fax 843-278-0001 | [www.aamsco.com](http://www.aamsco.com)





Commercial – Hospitality – Retail – Residential – Custom

**AAMSCO LIGHTING, INC.**

100 Lamp Light Circle | Summerville, SC 29483  
 Phone 843-278-0000 | Fax 843-278-0001 | www.aamsco.com

# Corncob Paddle LED



MODEL	LED28-PAD	LED30-PAD	LED60-PAD
Wattage	28W	30W	60W
Beam Angle	120 Degree	150 Degree	150 Degree
Light Source Count	28 LEDs	30 LEDs	54 LEDs
Lamp Base	Medium (MD) or Mogul (MG)	Mogul (MG)	Mogul (MG)
Power Consumption	31W +/-10%	33W +/-10%	67W +/-10%
Luminous Flux	2200lm	2500lm	4800lm
Color Temperature	WW 3000-3500K CW 4000-4500K D 6000-6500K	WW 3000-3500K CW 4000-4500K D 6000-6500K	WW 3000-3500K CW 4000-4500K D 6000-6500K
Input Voltage	100-280V	100-280V	100-280V
Life Hours	50,000	50,000	50,000
Dimensions	3.5" x 10.7"	4.25" x 10.7"	4" x 11.2"

**ORDERING CODE CONFIGURATION:**

LED(Watts)(Color Temp)(Base)-PAD

Example: LED28W 3000-3500K Medium Base = LED28WWMD-PAD

