

Corncob Mini



An energy smart alternative to incandescent lamps and an ecological light source to help the environment. Aamsco's Mini Corncob LEDs are an affordable light source for both residential and commercial areas.

Main Features:

- Fast turn on; no warm-up or cold start problems
- Estimated life hours: >50,000
- Sturdy PCB housing
- 80% more energy saving compared with conventional CFLs and incandescent lamps
- >85 CRI with great directionality
- 120 lumens per watt
- Universal burning positions

Specifications:

- Operating voltage: 100-277V
- Frequency range: 50-60hz
- Color Temperatures: WW3000-3500K, CW4000-4500K, D6000-6500K
- Integrated Heat-Sink Design
- 7 year warranty*
- UL, CE & ROHS Certified
- Not for use on a dimmer or remote controls
- For use in open or enclosed fixtures***

***In enclosed fixtures, ensure the lamp has enough space for heat dissipation. This will ensure lumen maintenance and extend its working life. When products are used in outdoor fixtures, ensure the space is waterproof and well ventilated. If there is a ballast in the existing fixture, simply disconnect or bypass when installing Corncob LED retrofit lamps.

Commercial – Hospitality – Retail – Residential – Custom

AAMSCO LIGHTING, INC.

100 Lamp Light Circle | Summerville, SC 29483

Phone 843-278-0000 | Fax 843-278-0001 | www.aamsco.com





Corncob Mini



MODEL	LED6W	LED9W	LED12W
Wattage	6W	9W	12W
Beam Angle	360 Degree	360 Degree	360 Degree
Light Source Count	133 LEDs	150 LEDs	180 LEDs
Lamp Base	Medium (MD)	Medium (MD)	Medium (MD)
Power Consumption	8W +/-10%	10W +/-10%	13W +/-10%
Luminous Flux	720lm	1080lm	1440lm
Color Temperature	WW 3000-3500K CW 4000-4500K D 6000-6500K	WW 3000-3500K CW 4000-4500K D 6000-6500K	WW 3000-3500K CW 4000-4500K D 6000-6500K
Input Voltage	100-277V	100-277V	100-277V
Life Hours	50,000	50,000	50,000
Dimensions	2" x 3.3"	1.9" x 4.9"	2.4" x 6"

ORDERING NUMBER CONFIGURATION:

LED(Watt)(color temp)(base type)
 Example: LED9W, 3000-3500K, medium base= LED9WWMD

Recommended minimum 6" diameter spacing in enclosed fixtures

